SPECIFICATIONS

Amarr ENTREMATIC

	CARRIAGE HOUSE DESIGN											TRADITIONAL DESIGN									
	AMARR CARRIAGE COURT CC4000	AMARR CLASSICA CL1000	AMARR CLASSICA CL2000	AMARR CLASSICA CL3000	AMARR OAK SUMMIT OS1000	AMARR OAK SUMMIT OS2000	AMARR OAK SUMMIT OS3000	AMARR HILLCREST HI1000	AMARR HILLCREST HI2000	AMARR HILLCREST HI3000	AMARR DESIGNER'S CHOICE DC3200	AMARR HERITAGE HR1000	AMARR HERITAGE HR2000	AMARR HERITAGE HR3000	AMARR STRATFORD ST1000	AMARR STRATFORD ST2000	AMARR STRATFORD ST3000	AMARR LINCOLN LI1000	AMARR LINCOLN LI2000	AMARR LINCOLN LI3000	AMARR OLYMPUS OL3200
PANEL DESIGNS (Safe Guard)		✓	✓	✓	✓	✓	✓					✓	✓	✓	✓	✓	✓				
Short												•	•	•	•	•	•	•	•	•	•
Long												•	•	•	•	•	•	•	•	•	•
Flush														•	•	•	•	•	•	•	TW only
Ribbed														•			•			•	
Carriage House	18 Designs	7 Designs	7 Designs	7 Designs	4 Designs	4 Designs	4 Designs	4 Designs	4 Designs	4 Designs	4 Designs										
CONSTRUCTION LAYERS	4	1	2	3	1	2	3	1	2	3	3	1	2	3	1	2	3	1	2	3	3
Steel		•			•			•				•			•			•			
Steel + Insulation			•			•			•				•			•			•		
Steel + Insulation + Steel				•			•			•	•			•			•			•	•
Overlay + Steel + Insulation + Steel	•																				
DOOR THICKNESS	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)
INSULATION	Polystyrene[1]		Polystyrene[1]	Polyurethane		Polystyrene[1]	Polystyrene[1]		Polystyrene[1]	Polystyrene[1]	Polyurethane		Polystyrene[1]	Polystyrene[1]		Polystyrene[1]	Polystyrene[1]		Polystyrene[1]	Polystyrene[1]	Polyurethane
R-VALUE[2]	6.48		6.64	13.35		6.64	6.48		6.64	9.05	19.40†/13.35**		6.64	9.05		6.64	6.48		6.64	9.05	19.40†/13.35‡
STEEL THICKNESS																					
Gauge (ga)	27/27 ga	24 ga	24 ga	25/27 ga	25 ga	25 ga	27/27 ga	25 ga	25 ga	27/27 ga	27/27 ga	24 ga	24 ga	24/27 ga	25 ga	25 ga	27/27 ga	25 ga	25 ga	27/27 ga	27/27 ga
Gauge (mm)	0.42/0.42mm	0.61mm	0.61mm	0.53/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.42/0.42mm	0.61mm	0.61mm	0.61/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.42/0.42mm
WOODGRAIN EXTERIOR TEXTURE	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•[6]	•[6]	•	•[6]	•[6]	•	•
GALVANIZED END STILES		•	•		•	•		•	•						•	•		•	•		
PAINTED END STILES	•			•			•			•	•	•	•	•			•			•	•
THERMAL SEAL	•						•				•*			•			•				•†
BOTTOM WEATHER SEAL																					
Steel Retainer		•	•	•	•	•		•	•		•**	•	•		•	•		•	•		•‡
Aluminum Retainer	•						•							•			•				
Extruded Vinyl										•	•*									•	•†
DECORATIVE WINDOW OPTIONS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WINDOW GLASS OPTIONS																					
3/32" (0.24cm) Single Strength					•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1/8" (0.32cm) Tempered 2X Strength	•	•	•	•																	
Clear Insulated	•			•			•			•	•			•			•			•	•
Obscure	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Frost		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Dark Tint		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
DECORATIVE HARDWARE OPTIONS	•	•	•	•	•	•	•	•	•	•	•										
EXTERIOR COLOR OPTIONS																					
True White (TW)	•[3]	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Almond (AL)	•[3]	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Wicker Tan (WK)	•[3]	•	•	•	•	•	•	•	•	•	•				•	•	•	•	•	•	•
Sandtone (ST)	•[3]	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Terratone (TT)		•	•	•	•	•	•	•	•	•					•	•	•	•	•	•	
Dark Brown (DN)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Hunter Green (HG)							•										•				
Gray (GY)							•										•				
Charcoal Gray (EF)		•	•	•				•	•	•								•	•	•	
Black (BL)		•	•	•							•	•	•	•							•
Golden Oak (OK)		•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	
Walnut (NT)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Mahogany (MY)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WIND LOAD[4] **AVAILABLE**	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
PAINT FINISH WARRANTY[5]	Lifetime	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	15 Years	25 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	15 Years	25 Years	Lifetime	Lifetime
WORKMANSHIP/HARDWARE WTY[5]	5 Years	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	1 Year	2 Years	3 Years	Lifetime	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	1 Year	2 Years	3 Years	Lifetime

✓ SAFE GUARD Pinch Protection Amarr ENTREMATIC

1 Insulation on Amarr brand doors has passed self-ignition, flamespread, and smoke developed index fire testing.

2 Calculated door section R-value is in accordance with DASMA TDS-163.

* True White Bead Board only. Based on independent laboratory test results.

** All panels and colors except True White Bead Board.

† True White Short and Flush panel designs only. Based on independent laboratory test results.

‡ All panels and colors except True White Short and Flush panel designs.

3 With White Overlay.

4 It is your responsibility to make sure your garage door meets local building codes.

5 For complete warranty details, visit amarr.com or contact your local Amarr dealer.

6 Flush Panel design has Stucco texture

NOTE: Optional door locks and various heights and widths are available thru your local garage door dealer.